

Solving Sequencing Problem Using Trapezoidal Fuzzy Numbers

K.Kripa¹ and R.Govindarajan²

¹St.Thomas College of Arts and Science, Chennai, India, PIN 600107

²Department of Mathematics, D G Vaishnav College, Chennai, India

¹Corresponding author. Email: mathskripakrishnan@gmail.com

Received 8 May 2016; accepted 14 May 2016

Abstract. In this paper, we present the different methods to solve fuzzy sequencing problem using fuzzy technological values like trapezoidal fuzzy numbers. The procedure adopted was the fuzzy sequencing problems are defuzzified using ranking functions and hence solving the crisp sequencing problem by standard sequencing algorithm for obtaining the optimal sequence and minimum completion time in terms of fuzzy values which is illustrated with numerical examples and solutions.

Keywords. Fuzzy sequencing problem, trapezoidal fuzzy numbers, fuzzy arithmetic and ranking functions.

AMS Mathematics Subject Classification (2010): 05C12, 03E72, 05C72

1. Introduction

Operations research is a problem solving and decision making Science. Modeling is the essence of operations research. Formulating a model help us to convert the complexities and uncertainties of a decision making problem to a logical model which is open to formal analysis. It also involves the application of scientific tools for finding optimum solution to the problem involving the operations of system.

A sequencing problem is to determine the optimal sequence in which 'n' jobs to be performed by 'm' machine and various optimality criteria like minimum elapsed time , minimum idle time , minimum inventory cost with the given conditions i) the order of the machine in which each job should be performed ii) the actual or expected time required by the jobs on each of the machine.

Sequencing have been most commonly encountered in production shops where different products are to be processed over various combinations of machines.

The complicated real life situations are defined in terms of impressions which was overcome by Zadeh with a powerful tool of fuzzy data. Thus fuzzy sequencing problem plays a vital role in formulating the uncertainty in actual environment.

This paper is framed as follows section2:Basic definitions and preliminary results, section 3:Application of ranking functions to solve Fuzzy sequencing problem(FSP) , section 4: Numerical examples illustrated with solutions and section 5: conclusion.

2. Preliminaries

Basic notations and preliminary results are referred from [1,2,3]

Definition 2.1. A fuzzy set $A = \{(x, \mu_A(x)) : x \in X\}$ is defined for $x \in X$ with respect to the membership function μ_A where μ_A is defined by $\mu_A : X \rightarrow [0,1]$

Definition 2.2. A fuzzy number \tilde{A} where $\tilde{A} = (a,b,c,d)$ is called **trapezoidal fuzzy number** if its membership function is given by

$$\mu_{\tilde{A}} = \begin{cases} \frac{(x-a)}{(b-a)}, & a \leq x \leq b \\ 1 & , b \leq x \leq c \\ \frac{(x-c)}{(c-d)}, & c \leq x \leq d \end{cases}$$

Definition 2.2.1. The **ranking function of trapezoidal fuzzy number** $\tilde{A} = (a,b,c,d)$ is given by $\mathfrak{R}(\tilde{A}) = \frac{2a+2b+d-c}{4}$ where $\tilde{A}=(a,b,c,d)$

Fuzzy arithmetic operations 2.2.2

Let $\tilde{A}=(a,b,c,d)$ and $\tilde{B}=(e,f,g,h)$ then

1. $\tilde{A} \oplus \tilde{B} = (a+e, b+f, c+g, d+h)$
2. $\tilde{A} \ominus \tilde{B} = (a-e, b-f, c-g, d-h)$

3. Application of ranking functions to solve fuzzy sequencing problem

3.1 Algorithm for solving fuzzy sequencing problem

3.1.1 Processing ‘n’ jobs through two machines

The simplest possible fuzzy sequencing decision problem is that of ‘n’ jobs two machine fuzzy sequencing problem is to determine the sequence in which ‘n’ jobs should be processed through two machines so as to minimize the total elapsed time T. This type of problem can be completely described as :

- i) only two machines \tilde{A} and \tilde{B} are involved
- ii) each job is processed in the order AB, and
- iii) the expected fuzzy processing time $\tilde{A}_i = (a_i, b_i, c_i, d_i)$ and $\tilde{B}_i = (x_i, y_i, z_i, w_i)$ where $i= 1,2,3,\dots,n$ are known as given below:

job	J1	J2	\tilde{J}_3	\tilde{J}_n
\tilde{A}_i	(a_1, b_1, c_1, d_1)	(a_2, b_2, c_2, d_2)	(a_3, b_3, c_3, d_3)	(a_n, b_n, c_n, d_n)
\tilde{B}_i	(x_1, y_1, z_1, w_1)	(x_2, y_2, z_2, w_2)	(x_3, y_3, z_3, w_3)	...	(x_n, y_n, z_n, w_n)

The procedure for the solution of the above problem is described as follows:

- Step 1: using ranking function the fuzzy sequencing problem is defuzzified into crisp sequencing problem
- Step 2: the optimal sequence for the crisp sequencing problem is determined using crisp sequencing algorithm
- Step 3: After finding the optimal sequence as stated above, the total elapsed fuzzy time and also the fuzzy idle times on machines \tilde{A} and \tilde{B} are determined as follows:

Solving Sequencing Problem Using Trapezoidal Fuzzy Numbers

Step 4:**Total elapsed fuzzy time** = the fuzzy time between starting the first job in the optimal sequence on machine \tilde{A} and completing the last job in the optimal sequence on machine \tilde{B} .

Step 5:**Fuzzy idle time on machine \tilde{A}** = (fuzzy time when the last job in the optimal sequences is completed on Machine \tilde{B}) – (fuzzy time when the last job in the optimal sequence completed on machine \tilde{A})

Step 6:**Fuzzy idle time on machine \tilde{B}** = (fuzzy time when the first job in the optimal sequence completed on machine \tilde{A}) + $\sum_{k=2}^n$ [(fuzzy time when k^{th} job starts on machine \tilde{B}) – (fuzzy time $(k - 1)^{\text{st}}$ job finished on machine \tilde{B})]

3.1.2 Processing ‘n’ jobs through three machines

This type of problem can be completely described as :

i)only two machines \tilde{A} , \tilde{B} and \tilde{C} are involved

ii)each job is processed in the order $\tilde{A}\tilde{B}\tilde{C}$

iii) no passing of jobs is permitted , and

iii) the expected fuzzy processing time $\tilde{A}_i = (a_i, b_i, c_i, d_i)$, $\tilde{B}_i = (x_i, y_i, z_i, w_i)$,

$\tilde{C}_i = (e_i, f_i, g_i)$ where $i= 1,2,3\dots n$ are known as given below:

job	J1	J2	J3	Jn
\tilde{A}_i	(a_1, b_1, c_1, d_1)	(a_2, b_2, c_2, d_2)	(a_3, b_3, c_3, d_3)	(a_n, b_n, c_n, d_n)
\tilde{B}_i	(x_1, y_1, z_1, w_1)	(x_2, y_2, z_2, w_2)	(x_3, y_3, z_3, w_3)	...	(x_n, y_n, z_n, w_n)
\tilde{C}_i	(e_1, f_1, g_1, h_1)	(e_2, f_2, g_2, h_2)	(e_3, f_3, g_3, h_3)	(e_n, f_n, g_n, h_3)

The procedure for the solution of the above problem is described as follows:

Step 1: using ranking function the fuzzy sequencing problem is defuzzified into crisp sequencing problem

Step 2: the optimal sequence for the crisp sequencing problem of Processing ‘n’ jobs through three machines is determined using crisp sequencing algorithm.

The resulting optimal sequence will also be optimal for the original problem of 3 machines and n jobs. The total elapsed fuzzy time and also the fuzzy idle times on machines \tilde{A} , \tilde{B} and \tilde{C} are determined as follows:

Step 3:**Total elapsed fuzzy time** = the fuzzy time between starting the first job in the optimal sequence on machine \tilde{A} and completing the last job in the optimal sequence on machine \tilde{C} .

Step 4:**Fuzzy idle time on machine \tilde{A}** = (fuzzy time when the job J1 is completed on Machine \tilde{C}) – (fuzzy time when the last job is completed on machine \tilde{A})

Step5:**Fuzzy idle time on machine \tilde{B}** = (fuzzy time when the first job $\tilde{J}3$ is completed on machine \tilde{A}) + $\sum_{k=2}^n$ [(fuzzy time when k^{th} job on machine \tilde{B}) – (fuzzy time out for $(k - 1)^{\text{st}}$ job on machine \tilde{B})] + [fuzzy time last job is completed on \tilde{C} – fuzzy time last job is completed on \tilde{B}]

Step 6:**Fuzzy idle time on machine \tilde{C}** = (fuzzy time when the first job $\tilde{J}3$ is completed on machine \tilde{B}) + $\sum_{k=2}^n$ [(fuzzy time when k^{th} job on machine \tilde{C}) – (fuzzy time out for $(k - 1)^{\text{st}}$ job on machine \tilde{C})].

3.1.3/ Processing ‘n’ jobs through m machines

This type of problem can be completely described as :

i)there are n jobs denoted by J1,J2,J3,.....Jn to be performed

K.Kripa and R.Govindarajan

- ii) each job is processed through m machines $\tilde{A}_1, \tilde{A}_2, \tilde{A}_3, \dots, \tilde{A}_m$ in the order $\tilde{A}_1 \tilde{A}_2 \tilde{A}_3, \dots, \tilde{A}_m$
- iii) no passing of jobs is permitted
- iv) the expected fuzzy processing time are known as given below:

Job	Machines				
	\tilde{A}_1	\tilde{A}_2	\tilde{A}_3	\tilde{A}_m
J1	$(a_{11}, b_{11}, c_{11}, d_{11})$	$(a_{12}, b_{12}, c_{12}, d_{12})$	$(a_{13}, b_{13}, c_{13}, d_{13})$	$(a_{1m}, b_{1m}, c_{1m}, d_{1m})$
J2	$(a_{21}, b_{21}, c_{21}, d_{21})$	$(a_{22}, b_{22}, c_{22}, d_{22})$	$(a_{23}, b_{23}, c_{23}, d_{23})$	$(a_{2m}, b_{2m}, c_{2m}, d_{2m})$
J3	$(a_{31}, b_{31}, c_{31}, d_{31})$	$(a_{32}, b_{32}, c_{32}, d_{32})$	$(a_{33}, b_{33}, c_{33}, d_{33})$	$(a_{3m}, b_{3m}, c_{3m}, d_{3m})$
.					
Ji	$(a_{i1}, b_{i1}, c_{i1}, d_{i1})$	$(a_{i2}, b_{i2}, c_{i2}, d_{i2})$	$(a_{i3}, b_{i3}, c_{i3}, d_{i3})$	$(a_{im}, b_{im}, c_{im}, d_{im})$
.....					
Jn	$(a_{n1}, b_{n1}, c_{n1}, d_{n1})$	$(a_{n2}, b_{n2}, c_{n2}, d_{n2})$	$(a_{n3}, b_{n3}, c_{n3}, d_{n3})$	$(a_{nm}, b_{nm}, c_{nm}, d_{nm})$

The procedure for the solution of the above problem is described as follows:

Step 1: using ranking function the fuzzy sequencing problem is defuzzified into crisp sequencing problem

Step 2: the optimal sequence for the crisp sequencing problem of Processing 'n' jobs through m machines is determined using crisp sequencing algorithm.

The resulting optimal sequence will also be optimal for the original problem. The total elapsed fuzzy time and also the fuzzy idle times on machines are also determined

4. Numerical examples illustrated with solutions using trapezoidal fuzzy numbers

4.1 Type I : Fuzzy Sequencing for 5 jobs on 2 machines

Example 1. A book binder has one printing press, one binding machine and manuscripts of a number of different books. The time required to perform the printing and binding operation for each book are shown below. We wish to determine the order in which books should be processed, in order to minimize the total time(in hrs) required to turn out all the books

Books:	B1	B2	B3	B4	B5
Printing time:	(8,10,12,16)	(2,2,2,2)	(16,18,20,24)	(4,6,8,12)	(18,20,22,26)
Binding time:	(2,4,6,10)	(10,12,16,20)	(12,14,16,20)	(14,16,18,22)	(6,8,10,14)

Solution:

Using ranking function for trapezoidal fuzzy number given fuzzy sequencing problem is converted in crisp problem and the optimal sequence is obtained by standard sequencing algorithm

The sequence of the books is given by

B2	B4	B3	B5	B1
----	----	----	----	----

The fuzzy optimum time for completing all the books and the idle time for printing and binding is given in the following table:

Solving Sequencing Problem Using Trapezoidal Fuzzy Numbers

Book	Printing		Binding		Idle time for printing	Idle time For binding
	In time	Out time	In time	Out time		
B2	(0,0,0,0)	(2,2,2,2)	(2,2,2,2)	(12,14,18,22)	-	(2,2,2,2)
B4	(2,2,2,2)	(6,8,10,14)	(12,14,18,22)	(26,30,36,44)	-	-
B3	(6,8,10,14)	(22,26,30,38)	(26,30,36,44)	(38,44,52,64)	-	-
B5	(22,26,30,38)	(40,46,52,64)	(40,46,52,64)	(46,54,62,78)	-	(2,2,0,0)
B1	(40,46,52,64)	(48,56,64,80)	(48,56,64,80)	(50,60,70,90)	(2,4,6,10)	(2,2,2,2)
				Total	(2,4,6,10)	(6,6,4,4)

The optimum (minimum) time required to turn out all the books is **(50,60,70,90)** hrs

The idle time for printing is **(2,4,6,10)** hours

The idle time for binding is **(6,6,4,4)** hours

4.2. Type II : Fuzzy Sequencing for 5 jobs on 3 machines

Example 2.

Job :	J1	J2	J3	J4	J5
Machine \tilde{A} :	(2,6,8,12)	(4,8,10,14)	(4,6,8,12)	(6,10,12,14)	(2,6,8,12)
Machine \tilde{B} :	(2,2,2,2)	(1,1,1,1)	(2,4,6,10)	(2,6,8,12)	(3,3,3,3)
Machine \tilde{C} :	(3,3,3,3)	(4,8,10,14)	(2,6,8,12)	(4,6,8,12)	(4,8,10,14)

Solution:

Using ranking function for trapezoidal fuzzy number given fuzzy sequencing problem is converted in crisp problem and the optimal sequence is obtained by standard sequencing algorithm

The sequence of the jobs is given by

J2	J5	J4	J3	J1
----	----	----	----	----

The fuzzy optimum time for completing all the jobs and the idle time for the two machines is given in the following table:

Job	Machine \tilde{A}	Machine \tilde{A}	Machine \tilde{B}	Machine \tilde{B}	Machine \tilde{C}	Machine \tilde{C}
	In time	Out time	In time	Out time	In time	Out time
J2	(0,0,0,0)	(4,8,10,14)	(4,8,10,14)	(5,9,11,15)	(5,9,11,15)	(9,17,21,29)
J5	(4,8,10,14)	(7,11,14,16)	(6,14,18,26)	(9,17,21,29)	(9,17,21,29)	(13,25,31,43)
J4	(6,14,18,26)	(12,24,30,42)	(12,24,30,42)	(14,30,38,54)	(14,30,38,54)	(18,36,46,66)
J3	(12,24,30,42)	(16,30,38,54)	(16,30,38,54)	(18,34,44,64)	(18,34,44,64)	(20,42,54,78)
J1	(16,30,38,54)	(18,36,46,66)	(18,36,46,66)	(20,38,48,68)	(20,38,48,68)	(23,45,57,81)

	Idle time	Idle time	Idle time
	\tilde{A}	\tilde{B}	C
	-	(4,8,10,14)	-
	-	(1,5,7,11)	(5,9,11,15)
	-	(3,7,9,13)	-
	-	(2,0,0,0)	(1,5,7,11)
	(5,9,11,15)	(0,2,2,2)	-
		(3,7,11,15)	-
Total	(5,9,11,15)	(13,29,39,55)	(6,14,18,26)

K.Kripa and R.Govindarajan

The optimum (minimum) time required to finish all the jobs is **(23,45,57,81) hours**

The idle time for machines \tilde{A} is **(5,9,11,15)hours**

The idle time for machines \tilde{B} is **(13,29,39,55)hours**

The idle time for machines \tilde{C} is **(6,14,18,26)hours**

4.3. Type III : Fuzzy Sequencing for 4 jobs on 5 machines

Example 3.

Job	Machine				
	\tilde{A}	\tilde{B}	\tilde{C}	\tilde{D}	\tilde{E}
J1	(6,10,12,16)	(4,8,10,14)	(2,4,6,10)	(2,6,8,12)	(8,12,14,18)
J2	(6,8,10,14)	(6,8,10,14)	(4,6,8,12)	(4,8,10,14)	(10,12,16,20)
J3	(4,8,10,14)	(4,6,8,12)	(4,8,10,14)	(6,8,10,14)	(8,10,12,16)
J4	(8,10,12,16)	(2,6,8,12)	(2,4,6,10)	(2,4,6,10)	(6,8,10,14)

Solution:

Using ranking function for trapezoidal fuzzy number given fuzzy sequencing problem is converted in crisp problem and the optimal sequence is obtained by standard sequencing algorithm

The sequence of the jobs is given by

J1	J3	J2	J4
----	----	----	----

The fuzzy optimum time for completing all the jobs and the idle time for the two machines is given in the following table:

Job	Machine \tilde{A}	Machine \tilde{A}	Machine \tilde{B}	Machine \tilde{B}	Machine \tilde{C}	Machine \tilde{C}
	In time	Out time	In time	Out time	In time	Out time
J1	(0,0,0,0)	(6,10,12,16)	(6,10,12,16)	(10,18,22,30)	(10,18,22,30)	(12,22,28,40)
J3	(6,10,12,16)	(10,18,22,30)	(10,18,22,30)	(14,24,30,42)	(14,24,30,42)	(18,32,40,56)
J2	(10,18,22,30)	(16,26,32,44)	(16,26,32,44)	(22,34,42,58)	(22,34,42,58)	(26,40,50,70)
J4	(16,26,32,44)	(24,36,44,60)	(24,36,44,60)	(26,42,52,72)	(26,42,52,72)	(28,48,60,84)

Job	Machine \tilde{D}	Machine \tilde{D}	Machine \tilde{E}	Machine \tilde{E}
	In time	Out time	In time	Out time
J1	(12,22,28,40)	(14,28,36,52)	(14,28,36,52)	(22,40,50,70)
J3	(18,32,40,56)	(24,40,50,70)	(24,40,50,70)	(32,50,62,86)
J2	(26,40,50,70)	(30,48,60,84)	(32,50,62,86)	(42,62,78,106)
J4	(30,48,60,84)	(32,52,66,94)	(42,62,78,106)	(48,70,88,120)

	Idle time	Idle time	Idle time	Idle time	Idle time
	\tilde{A}	\tilde{B}	\tilde{C}	\tilde{D}	\tilde{E}
J1	-	(6,10,12,16)	(10,18,22,30)	(12,22,28,40)	(14,28,36,52)
J3	-	-	(-26,-4,8,30)	(-34,-4,12,42)	(-46,-10,10,48)
J2	-	(-26,-4,8,30)	(-34,-6,10,40)	(-44,-10,10,46)	-
J4	(24,34,44,60)	(-34,-6,10,38)	(-44,-8,8,46)	-	-
		(-24,18,46,94)	(-36,10,40,94)	(-46,4,36,88)	
Total	(24,34,44,60)	(-78,18,76,78)	(-130,10,88,240)	(-112,12,86,216)	(-32,18,46,100)

The optimum (minimum) time required to finish all the jobs is **(48,70,88,120)hours**

Solving Sequencing Problem Using Trapezoidal Fuzzy Numbers

The idle time for machines \tilde{A} is (24,34,44,60)hours

The idle time for machines \tilde{B} is (-78,18,76,78) hours

The idle time for machines \tilde{C} is (-130,10,88,240) hours

The idle time for machines \tilde{D} is (-112,12,86,216)hours

The idle time for machines \tilde{E} is (-32,18,46,100)hours

5. Conclusion

Fuzzy sequencing problem is solved by classical approach after defuzzification , which is easy to understand , helps to formulate uncertainty in actual environment and also serves as application for the decision makers in real life situation.

REFERENCES

1. M. Jayalakshmi and P.Pandian, A new method for finding an optimal fuzzy Solution for fully fuzzy linear programming problem, *International Journal of Engineering Research and Applications*, 2(4) (2012) 247-254.
2. A.Kumar, P.Singh, P.Kaur and A.P.Kaur, Generalized simplex algorithm to solve fuzzy linear programming problem with ranking of generalized fuzzy numbers, *Turkish Journal of Fuzzy System*, 1(2) (2010) 80-103.
3. A.Kumar, P.Singh, P.Kaur and A.P.Kaur, A new method for solving fully fuzzy linear programming problem, *Applied Mathematical Modeling*, 35 (2011) 817-823.